

4200 SLIDING TB



Transmittance

$U_w \geq 1.5$ (W/m²K)

Consult typology, dimensions and glass.

Acoustic insulation

Maximum glazing	26 mm
Minimum glazing	6 mm
Maximum acoustic insulation	Rw = 39 dB

Sightlines

Frame	60, 65, 77, 80 mm
	106, 126 mm 3 rails
Sash	33 / 37 mm

Profile Thickness

Door	1.5 mm
------	--------

Polyamide strip length

14.6 - 20 mm

Maximum sash dimensions

Width (L) = 2,200 mm

Height (H) = 2,600 mm

Consult maximum dimensions according to typologies.

Maximum sash weight

100 kg	45° sash encounter
200 kg	90° sash encounter

Consult maximum weight according to typologies.

Categories achieved at test centre

Protection against atmospheric agents.

Air permeability

(UNE-EN 12207): Class 3

Watertightness

(UNE-EN 12208): Class 7A

Wind resistance

(UNE-EN 12210): Class C5

* Reference test 1.26 x 1.26 m / 2 sashes.

Test verified by

ALUMINIOS CORTIZO S.A.U.

Extrusion alloy

6063 T-5

Finishes

Possibility of dual colour.

Colour powder coating (RAL, mottled & rough).

According to Qualicoat >60 microns

Wood effect powder coating.

According to Qualideco standard

Anodising.

According to Ewwa Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Sliding with 2, 3, 4 & 6 sashes.

Possibility of 3 rails.

1 & 2 rails pocket sliding door of 1,2 & 4 sashes.

