

Transmittance **$U_w \geq 1.0$ (W/m²K)**

Consult typology, dimensions and glass.

Acoustic insulation

Maximum glazing	41 mm
Minimum glazing	5 mm
Maximum acoustic insulation	Rw = 46 dB

Sightlines

Frame	54 mm
Sash	63 mm

Profile Thickness

Window	1.5 mm
Door	1.7 mm

Polyamide strip length 24 mm**Maximum dimensions / Sash**

Width (L) = 1,500 mm

Height (H) = 2,400 mm

Consult maximum weight and dimensions according to typologies.

Maximum weight / Sash 120 kg**Categories achieved at test centre**

Protection against atmospheric agents.

Air permeability**(UNE-EN 12207): Class 4****Water tightness****(UNE-EN 12208): Class E1200****Wind resistance****(UNE-EN 12210): Class C5**

* Reference test 1.20 x 1.20 m / 2 sashes.

Test verified by

ALUMINIOS CORTIZO S.A.U.**Extrusion alloy** 6063 T-5**Finishes**

Possibility of dual colour

Colour powder coating (RAL, mottled & rough)

According to Qualicoat >60 microns

Wood effect powder coating

According to Qualideco standard

Anodised

According to Ewva Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Inward opening: side hung, tilt & turn, parallel sliding and bottom hung.

Outward opening: side hung and top hung projecting.

